

## Color & Seal Exterior Solvent-Based Solid Color Concrete Sealer

Satin • 6920

### Product Description

Tropicrete Color & Seal is a deep penetrating high solids solvent-based acrylic concrete sealer. Designed to seal, protect and beautify concrete floors, decks, sidewalks, walkways, balconies, and pool decks. This product is easy to apply, dries fast and also protects concrete from spalling, staining and water intrusion. Tropicrete Color & Seal provides a dust-free surface; making it easier to maintain shop and warehouse floors. Its low satin sheen makes it easy to apply even, uniform coats.

<p><b>Recommended Substrates: Concrete</b></p> <ul style="list-style-type: none"> <li>• Driveways &amp; carports</li> <li>• Patios &amp; walkways</li> <li>• Garage &amp; warehouse floors</li> <li>• Swimming pool decks</li> </ul> <p><b>Product Features</b></p> <ul style="list-style-type: none"> <li>• Low sheen, solvent acrylic formula</li> <li>• Penetrates &amp; seals</li> <li>• Fast dry</li> <li>• Prevents moisture penetration</li> <li>• Weather &amp; wear resistant</li> </ul> <p>Available bases   6920: WB   DB   AB *</p> <p>Available colors   6924 Bombay</p> <p>Available colors   6925 Gull Grey</p> <p>Available colors   6926 Sandstone</p> <p>Available colors   6927 Pearl Grey</p> <p>Available colors   6928 Natural Concrete</p> <p>Available colors   6929 Clear**</p> <p>*Supporting the TropiCrete color card</p> <p><b>** Special order only</b></p>	<p><b>Application:</b> Brush, roller, airless or conventional spray</p> <p>Dry time @ 50% RH*: 15 - 35 Min to touch 4 - 6 HRS to recoat 3 Days for vehicle traffic</p> <p>*dry times listed may vary according to the relative humidity, temperature, film build, color and air movement of the application environment</p> <p>Flash Point: &gt;81°F, Flammable</p> <p>Clean Up: Xylene</p> <p><b>Product Limitations</b></p> <p>For best results, apply to bare, properly prepared concrete surfaces. If applied over a water-based sealer this application may blister or peel. Do not apply in direct sunlight; as hot surface temperatures could cause sealer to blister. Not recommended for previously painted surfaces or for immersion service. Do not apply if rain is expected within 12 hours following application.</p>	<p><b>Product Data</b></p> <p>Product Type: <b>Proprietary Solvent Acrylic</b></p> <p><b>6920</b></p> <p>Gloss @60°: 10</p> <p>Wt Solids ±4%: 52%</p> <p>Vol Solids ±2%: 35%</p> <p>Wet Film Mils: 4.0 - 5.3</p> <p>Dry Film Mils: 1.6 - 2.2</p> <p>Coverage / Gal * 250 - 350</p> <p>* coverage and wet and dry millage will vary by substrate type and porosity.</p> <p>VOC gms p/L **: &lt;582</p> <p>** less exempt solvents and before the addition of colorant</p> <p>Viscosity KU ±5: 63</p>
---	---	---

**Surface Preparation:** WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**General Surface Preparation:** The entire surface area to be sealed should be clean, dry, sound, and free from dirt, grease, oils, waxes, mildew, curing compounds, release agents, efflorescence, and any other surface contaminants that may adversely affect the performance of this coating material. For best results, pressure wash with a minimum 2000 psi pressure washer, or manually scrub substrate with a TSP or non-ammoniated detergent solution to remove contaminants. Repeat if surface contaminants remain.

**Mildew:** Surface areas affected by mildew should be treated with a commercial mildew removal and or wash product carefully following manufacturer's application and safety directions. Rinse thoroughly with clean water, and allow a minimum of 24 hours to dry thoroughly.

**Masonry / Concrete:** All new masonry surfaces should be allowed 30 - 90 days to properly dry/cure in accordance with industry standards. The surface should be tested for pH and alkali levels. Surface should not read higher than 8.5 - 9 level. Surface areas that register a reading higher than a 9 pH level may contain a high alkali level and should be etched with a solution of Muriatic Acid. To etch the floor, use a mixture of one (1) part muriatic acid mixed with three (3) parts water. Be sure to wear personal protection gear (goggles, gloves, boots, etc.) and follow the manufacturer's instructions and safety precautions when working with muriatic acid. Working in sections (10' x 10'), apply a generous amount of the acid solution with a plastic sprinkling can, and allow the solution to effervesce until it stops reacting. Rinse the surface thoroughly with a garden hose, not allowing the acid to dry on the surface. Test the pH again. This process should create a surface texture similar to that of 120 grit sandpaper, or the etching process must be repeated. Allow the floor to dry for at least 24 hours. Before painting, test the floor for excessive moisture by applying a 2' x 2' sheet of plastic to the floor with duct tape and allow it to set for 24 hours. If water droplets appear on the underside of the plastic, or the concrete appears wet (darker in color), the moisture content of the floor is too high and should not be painted.

**Painted Surfaces:** Surfaces that are painted will need to have the existing coating completely removed by hand tool cleaning methods, such as hand scraping, sanding, wire brushing, by power tool cleaning methods, such as electric sanders, floor grinders, commercial shot blasters, or by commercial chemical strippers.

**Surface Repairs:** Repair/replace all damaged, deteriorated and surface imperfections with the proper cementitious patching compounds or building materials.

**Application:** Can be easily applied with a quality brush, roller cover, or airless spray equipment as follows; stir thoroughly in a spiral up and down motion before and during application to keep product completely mixed. Roller application; apply using a smooth - medium nap (3/8" to 3/4") shed resistant roller cover, depending on the texture and surface porosity. Brush application; apply using a quality synthetic or China bristle brush. Surfaces to be painted should be completely dry for 24 hours before application. For best results, it is recommended to apply two (2) finish coats. Avoid heavy build-up of coating material. To assure color uniformity intermix multiple containers of custom tinted and stock colors. Apply a small test sample to verify color. Always apply product to a natural break in the surface, such as a corner or edge. When applying by brush, apply a smooth and generous coat on smaller surface areas, such as cutting-in larger surfaces and trim. When applying by roller cover, apply an even and generous coat in a "W" or crisscross motion, avoiding any excessive respreading or reworking. When applying by airless spray equipment use a unit with a minimum of 2000 psi of pressure, with a 0.013" - 0.015" fluid spray tip. During spray application, it is recommended to back-roll the surface area to ensure proper adhesion, an even coat application, and to work coating into surface pores. Always maintain a wet edge during application by brushing, rolling or spraying into previously applied coating area. Apply when surface and ambient temperatures are above 55°F and below 100°F. Avoid exterior paint application when weather conditions are threatening, and late in the day when there is a threat of moisture condensing on wet surface.

**Thinning:** Stir thoroughly and apply as it comes from the container. Thinning is not necessary. **Do Not Thin!**

**Clean Up:** Clean up any minor spills and spatters immediately with xylene, as well as all tools and airless equipment. More serious spills should be contained and removed with inert absorbent material. Dispose of contaminated absorbent, container, and unused.

### SAFETY - KEEP OUT OF REACH OF CHILDREN! FLAMMABLE! CONTAINS XYLENE!

Keep away from heat, sparks, and open flames. Prevent build-up of vapors by opening all windows and doors to achieve proper cross-ventilation. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during and until all vapors are gone. **USE WITH ADEQUATE VENTILATION!** Do not breathe dusts, vapors, or spray mists. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor / mist levels are above applicable levels, wear an appropriately fitted respirator, (NIOSH approved), during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eye, skin and clothing. Use chemical safety glasses, goggles, or a face shield for proper eye protection. Wash thoroughly after handling, and before eating or smoking. Close container after each use. **DO NOT TAKE INTERNALLY!** Refer to SDS for additional health and safety information.

### Storage and Disposal

Product should be kept from freezing temperatures or temperatures above 95°F. Refer to your local city or county government for instructions on disposal options.

Florida Paints believes the technical data represented in this technical bulletin to be current and up to date. However, Florida Paints makes no warranties or guarantees either expressed or implied. Florida Paints claims no responsibility from damages incurred from use by either the purchaser or user of the product.

PDS 6920 2007



Please excuse the small print used on this document but most paint company datasheets are two pages long. By squeezing all this information on one page we are doing our part to save a few trees.

**Florida Paints and Coatings, LLC**  
 78 3rd Street | Winter Garden, Florida 34787  
 407.986.1000 | [info@FloridaPaints.com](mailto:info@FloridaPaints.com) | [FloridaPaints.com](http://FloridaPaints.com)