



# FLORIDA PAINTS

## SAFETY DATA SHEET

### SDS FORM 1: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS

The following Safety Data Sheet (SDS) is being provided pursuant to requirements of the Fed/OSHA (29 CFR 1910.1200) and Cal/OSHA (8 CCR 5194) Hazard Communication Standards. The health and hazards information given here is based on data believed to be accurate by Florida Paints; we do not, however, assume any liability for the accuracy or completeness of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones that may exist. All persons intending to rely on any recommendation, or to use any technique, equipment, or material mentioned should first satisfy themselves that they can meet all applicable safety and health standards.

The following SDS supersedes any previously issued SDS for each product covered. The reader is advised to destroy any obsolete SDS and refer only to this SDS. As permitted by OSHA, each SDS may apply to a class of products, which have similar hazards and contents.

Exterior Products covered by this SDS are listed below:

1100	Legacy Flat
1120	Legacy Satin
1130	Legacy Semi-Gloss
1170	Legacy RainBright Exterior Self-Cleaning 100% Acrylic Flat
1180	Legacy RainBright Exterior Self-Cleaning 100% Acrylic Satin
1190	Legacy RainBright Exterior Self-Cleaning 100% Acrylic Semi-Gloss
1200	Seaside Flat
1220	Seaside Satin
1300	Glades Flat
1310	Glades Velvet Sheen
1320	Glades Satin
1330	Glades Semi-Gloss
1400	Reliance Flat
1420	Reliance Satin
1600	ClimaFlex Flat
1620	ClimaFlex Satin
1700	Pro-Exterior Latex Wall & Trim Paint
1800	SunFlex Flat
1820	SunFlex Satin
1180	SunFlex RainBright Exterior Self-Cleaning 100% Acrylic Hi-Build Satin
1940	TropiTex Acrylic Texture – Sand Finish
1950	TropiTex Acrylic Texture – Fine Finish
1960	TropiTex Acrylic Texture – Medium Finish
1990	TropiFlex XL Hi-Build Elastomeric Coating
5330	Aquatra+ Int/Ext Rust Inhibitive Acrylic DTM Enamel – Semi-Gloss
6020	TropiCrete Acrylic Deck Coating
6065	TropiCrete Acrylic Resin Fortifier 32%
6066	TropiCrete Acrylic Resin Fortifier 46%
6068	TropiCrete DuraDek Stamp Resin
6085	TropiCrete Slow Down Topping Retarder
6086	TropiCrete Speed Up Topping Accelerator
6120	TropiCrete Heavy Duty Acrylic Deck Coating (DISCONTINUED)
8180	GameOn Exterior Acrylic Field Marking Paint
8709	Rail Line Fence Paint
8990	#2001 White Super-Flex 100% Acrylic Elastomeric Roof Coating
8995	Super-Flex 100% Acrylic Elastomeric Roof Coating – Gray
8997	Super-Flex 100% Acrylic Elastomeric Roof Coating – Red
9101	Shade Int/Ext Concentrated WB Latex Greenhouse Shade Paint

# SAFETY DATA SHEET

## FORM 1: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS



---

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

---

PRODUCT IDENTIFICATION: SEE COVER PAGE FOR LIST OF PRODUCTS COVERED      MANUFACTURER: FLORIDA PAINTS AND COATINGS  
78 THIRD STREET  
WINTER GARDEN, FL 34787

PRODUCT TYPE: WATERBORNE PAINT

RECOMMENDED USE: ARCHITECTURAL COATING      CHEMTEL, INC      EMERGENCY PHONE      800.255.3924  
INTERNATIONAL      +1 813.248.0585

HMIS CODES:      H      F      R      PP      OTHER CALLS:      407.986.1000  
                  0      0      0      E      FAX NUMBER:      407.293.4233

---

### SECTION 2: HAZARDS IDENTIFICATION

---

GHS CLASSIFICATION: (NOT APPLICABLE)

GHS LABEL ELEMENTS: [NOTE: THIS CONSUMER PRODUCT IS EXEMPT FROM OSHA GHS-HCS LABELING REQUIREMENTS.]

SIGNAL WORD: (NONE REQUIRED)      HAZARD STATEMENT: (NONE REQUIRED)

PICTOGRAM: (NONE REQUIRED)

PRECAUTIONARY STATEMENTS:

PREVENTION: DO NOT INGEST. USE ONLY WITH ADEQUATE VENTILATION OR PROTECTION. AVOID BREATHING SPRAY MIST. AVOID CONTACT WITH EYES AND SKIN. CLOSE CONTAINER AFTER USE. KEEP OUT OF REACH OF CHILDREN.

RESPONSE: CLEAN UP SPILLS WITH INERT ABSORBENT MATERIAL, SUCH AS CLAY GRANULES, PAPER OR CLOTH WIPES. ALLOW TO DRY BEFORE DISPOSAL.

STORAGE & DISPOSAL: KEEP ABOVE 40°F AT ALL TIMES. DISPOSE OF CONTAINER AND CONTENTS IN ACCORDANCE WITH APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

HAZARDS NOT OTHERWISE CLASSIFIED: NONE.

---

### SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

---

HAZARDOUS INGREDIENTS:

CHEMICAL NAME	COMMON NAME / SYNONYMS	CAS NUMBER	CONCENTRATION (%WT)
---------------	------------------------	------------	---------------------

NO REPORTABLE HAZARDOUS INGREDIENTS.

NOTE: POTENTIAL UNUSUAL ALLERGIC SENSITIVITY TO TRACE INGREDIENTS OF THIS PRODUCT CAN BE MINIMIZED BY FOLLOWING RECOMMENDED PROCEDURES FOR SAFE HANDLING, STORAGE, DISPOSAL, AND USE.

# SAFETY DATA SHEET

## FORM 1: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS



---

### SECTION 4: FIRST-AID MEASURES

---

EYES: FLUSH EYES WITH FRESH WATER FOR AT LEAST 15 MINUTES.

SKIN: WASH THOROUGHLY WITH SOAP AND WATER.

INGESTION: HAVE VICTIM DRINK ENOUGH FRESH WATER TO ENSURE DILUTION.

INHALATION: MOVE VICTIM TO FRESH AIR.

MOST IMPORTANT SYMPTOMS AND EFFECTS: MAY CAUSE MILD IRRITATION TO EYES AND SKIN, GASTROINTESTINAL AND RESPIRATORY TRACTS. SLIGHT DIZZINESS, NAUSEA AND HEADACHE POSSIBLE.

NOTES TO FIRST AID PROVIDERS: CALL FOR MEDICAL ASSISTANCE IF SYMPTOMS PERSIST.

---

### SECTION 5: FIRE-FIGHTING MEASURES

---

SUITABLE EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.

UNUSUAL FIRE AND EXPLOSION HAZARDS: LIQUID MATERIAL IS NON-COMBUSTIBLE, BUT DRIED FILMS ARE CAPABLE OF SUPPORTING COMBUSTION WHEN IN CONTACT WITH OPEN FLAMES. CLOSED CONTAINERS CAN DEVELOP INTERNAL PRESSURE AND MAY RUPTURE WHEN SUBJECTED TO EXTREME HEAT.

HAZARDOUS COMBUSTION PRODUCTS: COMBUSTION CAN PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE.

SPECIAL EQUIPMENT & PRECAUTIONS: USE SELF-CONTAINED BREATHING APPARATUS IN CONFINED SPACES. OBSERVE RECOMMENDED PROCEDURES FOR HANDLING ORDINARY COMBUSTIBLE MATERIALS.

---

### SECTION 6: ACCIDENTAL RELEASE MEASURES

---

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, EMERGENCY PROCEDURES: WEAR WATERPROOF GLOVES TO AVOID SKIN CONTACT. KEEP CHILDREN AND PETS AWAY FROM SPILLED LIQUID. PREVENT LIQUID FROM ENTERING DRAINS.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN UP: DIKE SPILLED LIQUID WITH INERT MATERIAL, SUCH AS CLAY GRANULES. SCOOP UP EXCESS LIQUID AND POUR INTO CONTAINER. USE PAPER OR CLOTH WIPES TO CLEAN UP SMALL SPILLS. ALLOW TO DRY BEFORE DISPOSAL.

---

### SECTION 7: HANDLING AND STORAGE

---

SAFE HANDLING PRECAUTIONS: KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT STACK CONTAINERS MORE THAN THREE HIGH. SECURE LOADS AGAINST SHIFTING DURING TRANSPORTATION. USE ONLY AN APPROPRIATE TOOL TO OPEN CONTAINERS.

SAFE STORAGE CONDITIONS: STORE IN COOL, WELL-VENTILATED AREA. MAINTAIN TEMPERATURE BETWEEN 40°F AND 90°F. AVOID EXPOSURE TO DIRECT SUNLIGHT, HEAT OR FLAME. INSPECT CONTAINERS FOR LEAKS PERIODICALLY. ROTATE STOCK, USE OLDER MATERIAL FIRST.

INCOMPATIBILITIES: DO NOT HANDLE OR STORE NEAR WATER-REACTIVE MATERIALS, STRONG OXIDIZERS, ACIDS OR ALKALIS.

**SAFETY DATA SHEET**  
**FORM 1: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS**




---

**SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION**

---

HAZARDOUS INGREDIENTS	CAS NUMBER	%WT	ACGIH				OSHA EXPOSURE LIMITS		VAPOR PRESS mmHg @ TEMP
			TLV/TWA	PPM	TWA	PPM	MG/M <sup>3</sup>	STEL	

NO REPORTABLE HAZARDOUS INGREDIENTS.

- ENGINEERING CONTROLS:** USE SIGNS OR BARRIERS TO RESTRICT ACCESS TO PAINTING WORK AREA.
- VENTILATION :** NORMAL AIR CIRCULATION SHOULD BE SUFFICIENT. OTHERWISE, USE PORTABLE FANS. ENSURE ADEQUATE VENTILATION DURING APPLICATION, DRYING AND CURING OF PAINT.
- RESPIRATORY PROTECTION:** FOR SPRAY APPLICATION, USE PARTICULATE FILTER MASK TO AVOID BREATHING SPRAY MIST. EXPOSED PERSONS WITH UNUSUAL ALLERGIC SENSITIVITY MAY NEED ORGANIC VAPOR RESPIRATOR (NIOSH/MSHA TC 23C OR EQUIVALENT).
- EYE PROTECTION:** USE SAFETY GLASSES, GOGGLES, OR FACE SHIELD TO PROTECT EYES.
- SKIN PROTECTION:** USE WATERPROOF GLOVES (LATEX, VINYL, RUBBER, OR NEOPRENE) TO AVOID SKIN CONTACT.
- OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** WATERPROOF HEADCOVERING AND GENERAL PROTECTIVE CLOTHING ARE RECOMMENDED FOR PROTECTION AS NECESSARY.
- WORK HYGIENIC PRACTICES:** WASH HANDS AND FACE BEFORE EATING OR DRINKING.

---

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

---

<b>APPEARANCE:</b>	OPAQUE LIQUID DISPERSION	<b>VAPOR PRESSURE:</b>	SAME AS WATER VAPOR
<b>ODOR:</b>	VERY MILD ODOR	<b>VAPOR DENSITY:</b>	SAME AS WATER VAPOR
<b>ODOR THRESHOLD:</b>	(NO INFORMATION AVAILABLE)	<b>SPECIFIC GRAVITY:</b>	~1.27 - ~1.39 (H2O = 1)
<b>SOLUBILITY IN WATER:</b>	PARTLY SOLUBLE		
<b>FREEZING POINT:</b>	0° C / 32° F	<b>PARTITION COEFFICIENT:</b>	(NO INFORMATION AVAILABLE)
<b>BOILING POINT:</b>	100° C / 212° F	<b>AUTO-IGNITION TEMP:</b>	(NOT APPLICABLE)
<b>FLASH POINT:</b>	(NOT APPLICABLE)	<b>DECOMPOSTION TEMP:</b>	(NO INFORMATION AVAILABLE)
<b>EVAPORATION RATE:</b>	SAME AS WATER	<b>VISCOSITY:</b>	100 - 115 KU
<b>FLAMMABILITY:</b>	(NOT APPLICABLE)	<b>PERCENT SOLIDS: BY VOL:</b>	~31% - ~44% BY WT: ~45% - ~58%
<b>UPPER EXPLOSIVE LIMIT:</b>	(NOT APPLICABLE)	<b>PERCENT VOLATILE: BY VOL:</b>	~69% - ~56% BY WT: ~55% - ~42h%
<b>LOWER EXPLOSIVE LIMIT:</b>	(NOT APPLICABLE)		

**SAFETY DATA SHEET**  
**FORM 1: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS**



---

**SECTION 10: STABILITY AND REACTIVITY**

---

REACTIVITY: REACTIVITY NOT KNOWN TO OCCUR UNDER NORMAL CONDITIONS.  
CHEMICAL STABILITY: STABLE UNDER NORMAL CONDITIONS.  
POSSIBILITY OF HAZARDOUS REACTIONS: POLYMERIZATION WILL NOT OCCUR.  
CONDITIONS TO AVOID: AVOID STORAGE OR USE AT TEMPERATURES BELOW 40° F.  
INCOMPATIBLE MATERIALS: AVOID WATER-REACTIVE MATERIALS, STRONG OXIDIZERS, ACIDS AND ALKALIS.  
HAZARDOUS DECOMPOSITION PRODUCTS: COMBUSTION CAN PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE.

---

**SECTION 11: TOXICOLOGICAL INFORMATION**

---

LIKELY ROUTES OF EXPOSURE: INHALATION, INGESTION, SKIN AND EYE CONTACT  
SYMPTOMS OF OVEREXPOSURE: MAY CAUSE MILD IRRITATION TO EYES AND SKIN, GASTROINTESTINAL AND RESPIRATORY TRACTS. SLIGHT DIZZINESS, NAUSEA AND HEADACHE POSSIBLE IN EXPOSED PERSONS WITH UNUSUAL ALLERGIC SENSITIVITY.  
DELAYED OR CHRONIC EFFECTS: AVAILABLE INFORMATION PROVIDES NO EVIDENCE OF DELAYED OR CHRONIC HEALTH EFFECTS ASSOCIATED WITH EXPOSURE.  
NUMERICAL MEASURES OF TOXICITY: (NO INFORMATION AVAILABLE)  
CARCINOGENICITY: NTP? NO. IARC? NO. OSHA? NO. PROP 65? NO.

\* Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

---

**SECTION 12: ECOLOGICAL INFORMATION**

---

ECOLOGICAL INFORMATION: (NO INFORMATION AVAILABLE)

---

**SECTION 13: DISPOSAL CONSIDERATIONS**

---

WASTE DISPOSAL METHOD: COLLECT SPILLED MATERIAL, USED ABSORBENT MATERIAL AND WIPES INTO A SUITABLE CONTAINER AND DISPOSE IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE, AND FEDERAL REGULATIONS. DRY, EMPTY CONTAINERS MAY BE RECYCLED OR DISPOSED OF AS ORDINARY TRASH.  
RCRA HAZARD CLASS: NON-HAZARDOUS

---

**SECTION 14: TRANSPORT INFORMATION**

---

THIS MATERIAL IS NOT SUBJECT TO DOT, IATA/ICAO, OR IMO/IMDG TRANSPORTATION REGULATIONS. ACCEPTABLE FOR AIR TRANSPORT AS NON-HAZARDOUS GOODS.

UN NUMBER: (NOT APPLICABLE) UN PROPER SHIPPING NAME: (NOT APPLICABLE)  
TRANSPORT HAZARD CLASS: (NOT APPLICABLE) PACKING GROUP: (NOT APPLICABLE)  
ENVIRONMENTAL HAZARDS: (NOT APPLICABLE) TRANSPORT IN BULK: (NOT APPLICABLE)

**SAFETY DATA SHEET**  
**FORM 1: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS**



SPECIAL PRECAUTIONS: FOLLOW RECOMMENDED PROCEDURES FOR SAFE HANDLING AND STORAGE.

---

**SECTION 15: REGULATORY INFORMATION**

---

U.S. FEDERAL REGULATIONS:

TSCA: ALL COMPONENTS ARE LISTED IN TSCA INVENTORY OR EXEMPT.

CERCLA: NOT LISTED AS A HAZARDOUS SUBSTANCE.

SARA TITLE III: NOT LISTED AS A HAZARDOUS SUBSTANCE.

311/312 HAZARD CATEGORIES: (NOT APPLICABLE)

313 REPORTABLE INGREDIENTS: (NOT APPLICABLE)

STATE REGULATIONS:

(NOT APPLICABLE)

California Proposition 65 Warning! This product contains a chemical known to the State of California to cause cancer. The listing of titanium dioxide is for airborne, unbound "particles of respirable size." The listing is not applicable to titanium dioxide when it remains bound within a product matrix, such as paint.

---

**SECTION 16: OTHER INFORMATION**

---

DATE OF PREPARATION: October 17, 2018

PREPARER INFORMATION: FLORIDA PAINTS  
PHONE: 407.986.1000

DISCLAIMER: THE INFORMATION CONVEYED ABOVE, ALTHOUGH OBTAINED FROM SOURCES WE CONSIDER RELIABLE, IS FURNISHED BY FLORIDA PAINTS WITHOUT ANY WARRANTY (WHETHER EXPRESS OR IMPLIED) AS TO ITS ACCURACY, ADEQUACY, OR APPLICABILITY TO ANY PARTICULAR NEEDS OR CIRCUMSTANCES.

---